

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Adhesive Spray KK 100

Revision date: 06.09.2023 Product code: VCSO-GD-012 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Adhesive Spray KK 100

UFI: FNPV-10RR-V00R-DKVY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

adhesives

Uses advised against

Only use for the intended purpose. In case of doubt please contact our responsible department.

1.3. Details of the supplier of the safety data sheet

Company name: GUNOLD GmbH

Street: Obernburger Straße 125
Place: D-63811 Stockstadt

Telephone: +49 (0)6027 - 2 00 80 Telefax: +49 (0)6027 - 37 72

E-mail: service@gunold.de

Contact person: Christoph Gunold Telephone: +49 (0)6027 - 2 00 80

E-mail: c.gunold@gunold.de lnternet: www.gunold.de

Responsible Department: Quality Control and Environment

1.4. Emergency telephone +353 1 8092566 (Healthcare Professionals) +353 1 8092166 (consumer | 8am –

number: 10pm | 7 days a week)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 1; H222-H229

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing Aerosol.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Do not discard content with household waste and forward for disposal according to



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Adhesive Spray KK 100

Revision date: 06.09.2023 Product code: VCSO-GD-012 Page 2 of 11

regional/national guidelines.

2.3. Other hazards

Prolonged/repetitive product contact may cause mucosa and skin irritation like redness, blistering, dermatitis etc.

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
115-10-6	dimethyl ether			50 - 70 %
	204-065-8	603-019-00-8		
	Flam. Gas 1, Compressed gas; H220 H280			
109-87-5	dimethoxymethane			5 - 7 %
	203-714-2		01-2119664781-31	
	Flam. Liq. 2; H225			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of troubles or persistent symptoms, consult an doctor/physician.

Remove persons from danger area and lie them down. Never orally infuse something to an unconscious person. No special first aid measures necessary. A vomiting, supine person must be brought into recovery position.

In case of irregular breathing or respiratory arrest, perform artificial respiration.

After inhalation

Provide fresh air.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Call a physician immediately. Do NOT induce vomiting.



according to Regulation (EC) No 1907/2006

Adhesive Spray KK 100

Revision date: 06.09.2023 Product code: VCSO-GD-012 Page 3 of 11

4.2. Most important symptoms and effects, both acute and delayed

Prolonged/repetitive product contact may cause mucosa and skin irritation like redness, blistering, dermatitis

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Water fog. Carbon dioxide (CO2).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Heating causes rise in pressure with risk of bursting.

Thermal decomposition can lead to harmful gases and vapours.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

See protective measures under point 7 and 8.

For non-emergency personnel

Keep away from sources of ignition - No smoking. Ventilate affected area. Do not breathe mist/vapours/spray.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of product being released into lakes, rivers or the drainage system, appropriate authorities must be informed.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Personal protection equipment: see section 8

Handling and storage: see section 7 For waste disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Consider the usual precautions for handling chemicals. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Avoid contact with skin and eyes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.



according to Regulation (EC) No 1907/2006

Adhesive Spray KK 100

Revision date: 06.09.2023 Product code: VCSO-GD-012 Page 4 of 11

Advice on general occupational hygiene

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink. Avoid contact with skin, eyes and clothes. After contact with skin, wash immediately with plenty of water and soap or a suitable cleaning agent.

Further information on handling

When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep only in the original container in a cool, well-ventilated place. Ensure adequate ventilation of the storage area.

Hints on joint storage

Do not store together with: Acid, concentrated. Alkalis, strong. Oxidising agent, strong. Keep away from food, drink and animal feedingstuffs. Protect from sunlight.

7.3. Specific end use(s)

adhesives

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
74-98-6	Aliphatic hydrocarbon gases, Alkanes (C1-C3), Propane	-	-		Asphyxiant	
75-28-5	Butane, all isomers - Isobutane	1000	-		STEL (15 min)	
106-97-8	Butane, all isomers - n-butane	1000	-		STEL (15 min)	
109-87-5	Dimethoxymethane	1000	3100		TWA (8 h)	
115-10-6	Dimethyl ether	1000	1920		TWA (8 h)	

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Wear chemically resistant gloves.

During handling of the mixture (production and storage): Wear suitable gloves.

Suitable gloves type

NBR (Nitrile rubber). (>= 0,4 mm; penetration time (maximum wearing period): >= 480 min)

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear anti-static footwear and clothing



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Adhesive Spray KK 100

Revision date: 06.09.2023 Product code: VCSO-GD-012 Page 5 of 11

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid (Aerosol)
Colour: various
Odour: characteristic

Melting point/freezing point:

Boiling point or initial boiling point and

No data available.

-42 °C

boiling range:

Flammability: No data available.

not applicable 1,4 vol. %

Lower explosion limits:

Upper explosion limits:

19,9 vol. %
Flash point:

-60 °C
Auto-ignition temperature:

Decomposition temperature:

No data available.

pH-Value:

No data available.

Viscosity / kinematic:

No data available.

Water solubility:

practically insoluble

Solubility in other solvents

No data available.

Partition coefficient n-octanol/water:

Vapour pressure:

No data available.

417,727 hPa

(at 20 °C)

Density (at 20 °C): 0,80 g/cm³
Relative vapour density: No data available.

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available.

Self-ignition temperature

Solid: No data available.

Gas: No data available.

Oxidizing properties

No data available.

Other safety characteristics

Evaporation rate:

Solvent content:

Solid content:

Sublimation point:

Softening point:

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Adhesive Spray KK 100

Revision date: 06.09.2023 Product code: VCSO-GD-012 Page 6 of 11

The product is stable when stored and handled appropriately.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidisers to avoid exothermic reactions.

10.4. Conditions to avoid

high temperature (above the decomposition temperature)

For further information concerning storage: see section 7.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

May form hazardous decomposition products when exposed to high temperatures.

Hazardous decomposition products: Carbon dioxide (CO2). Carbon monoxide. Smoke.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Adhesive Spray KK 100

Revision date: 06.09.2023 Product code: VCSO-GD-012 Page 7 of 11

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
115-10-6	dimethyl ether	0,1

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. According to the European Waste Catalogue (EWC), allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es): 2
14.4. Packing group: -

Hazard label: 2.1



Classification code: Special Provisions:

190 327 344 625



Safety Data Sheet

according to Regulation (EC) No 1907/2006

	Adhesive Spray KK 100	
Revision date: 06.09.2023	Product code: VCSO-GD-012	Page 8 of 11

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: 63, 190, 277, 327, 344, 381, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G Passenger LQ: Y203 Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No special precautions known.



according to Regulation (EC) No 1907/2006

Adhesive Spray KK 100

Revision date: 06.09.2023 Product code: VCSO-GD-012 Page 9 of 11

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40

2004/42/EC (VOC): 743,32 g/l

Information according to 2012/18/EU P3a FLAMMABLE AEROSOLS

(SEVESO III):

Additional information

Regulation (EC) No. 648/2004 [Detergents regulation]: not applicable

Regulation (EC) No. 1005/2009 on substances that lead to the depletion of the ozone layer: not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants: not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council concerning the export and import of dangerous chemicals: This mix contains no chemicals that are subject to the export notification procedures (annex 1).

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

This mixture contains the following substances of very high concern (SVHC) which are subject to authorisation according to Annex XIV of REACH: none

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out: dimethoxymethane

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,7,8,9,10,11,12,15,16.

Version 1,00 - Creation - 29.07.2011

Version 1,01 - changes of S-phrases - 02.08.2012

 $Version\ 1,02\ -\ revision\ of\ the\ entire\ SDS\ due\ to\ new\ information\ from\ the\ presupplier\ -\ 12.02.2013$

Version 1,03 - Classification/Labeling according Regulation No.1272/2008 (GHS/CLP) and general revision -

09.06.2015

Version 1,04 - General update - 12.09.2017

Version 1,05 - General update - 06.10.2021

Version 1,06 - General update - 06.09.2023



according to Regulation (EC) No 1907/2006

Adhesive Spray KK 100

Revision date: 06.09.2023 Product code: VCSO-GD-012 Page 10 of 11

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

BImSchV (Fed.Imm.Prot.Act): Directive on the Implementation of the Federal Immission Protection Act

CAS: Chemical Abstracts Service

DIN: Norm of the Deutsche Institut für Normung (German Institute for Standardization)

EC: Effective Concentration

EG: European Community (Europäische Gemeinschaft)

EN: European Norm

IATA: International Air Transport Association

IBC Code: International Code for the Construction and Equipment of ships carrying Dangerous Chemicals in

Bulk

ICAO: International Civil Aviation Organization

IMDG: International Maritime Code for Dangerous Goods ISO: Norm of the International Standards Organization

CLP: Classification, Labeling, Packaging

IUCLID: International Uniform Chemical Information Database

LC: Lethal concentration

LD: Lethal dose

log Kow: Octanol/water partition coefficient

MARPOL: Maritime Pollution Convention = Convention for the Prevention of Maritime Pollution from Ships

OECD: Organisation for Economic Co-operation and Development

PBT: Persistent, bio-cumulative, toxic

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail

TRGS: Technische Regeln für Gefahrstoffe

UN: United Nations

VOC: Volatile Organic Compounds

vPvB: very persistent and very bio-cumulative

WGK: German Water Hazard Class

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration

TLV: Threshold Limiting Value

STOT: Specific Target Organ Toxicity

AwSV: Ordinance on Installations for Handling Substances Hazardous to Water

Flam. Gas: Flammable gases

Aerosol: Aerosols

Compressed gas: Compressed gas Flam. Liq: Flammable liquid

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains das under pressure: may explode if he

H280 Contains gas under pressure; may explode if heated.

Further Information

The information given in this safety data sheet is to describe the product's safety regulations. It is not for guaranteeing certain characteristics and is based on today's knowledge. The safety data sheet was generated upon information of pre-suppliers by:



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Adhesive Spray KK 100

Revision date: 06.09.2023 Product code: VCSO-GD-012 Page 11 of 11

asseso AG, Ottostraße 1, 63741, Aschaffenburg, Germany

Phone: +49 (0)6021 - 1 50 86-0, Fax: +49 (0)6021 - 1 50 86-77, E-Mail: eu-sds@asseso.eu, www.asseso.eu

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)